



Product overview detectors

niko



Content

230 V outdoor

230 V motion

230 V presence

DALI

KNX

24 V

Index



Niko, comfort and quality in every home and work environment

In a world where everything is speeding up, your clients increasingly require a higher comfort level. Both in their work and living environment. With Niko, you can integrate limitless comfort into any living space.

After all, Niko designs and produces progressive solutions for electrical switching material, lighting control, home automation and access control. Both private and professional customers worldwide choose Niko's quality solutions because of their ease of installation, ease of use and design.

We're not only refreshing our products, we're also refreshing their technology. Our emphasis? It's on easy installation and programming. And naturally on quality and design.

In the catalogue, you can recognize the new products by their label **NEW**. Register at www.niko.eu for our newsletter to stay up-to-date about our newest products.

You don't find here what you are looking for? The most recent information can be found at any time at www.niko.eu.



We offer you 4 years warranty, while only 2 years are required by European law. The warranty period for all our products is 4 years from the delivery date. The invoice date is the delivery date. If ever the Niko hardware does not work - even though we have stringent quality controls – our customer service department is ready to help you at + 32 3 778 90 80 or via support.be@niko.eu.





230 V outdoor



Reference number

Description

7520

Twilight switch, 230 V, 5 lux – 1000 lux, IP55

Master/Secondary

Protection degree

Number of channels/
number of zones

Detection angle

Mounting height

Detection range

Commissioning method 1

Commissioning method 2

Commissioning method 3

Page

-

IP55

1 channel

-

-

-

On the device

8



Article number **Description****7520****Twilight switch, 230 V, 5 lux – 1000 lux, IP55**

N.O. (max. 4.35 A)



5 lux – 1000 lux



IP55



















The built-in light sensor measures the brightness of the surroundings. The light is automatically switched on below a programmable brightness threshold. A timer can be set for the light to be switched off (2 to 8 h), or the light can stay on permanently as long as the brightness threshold is not reached (D–D).



































230 V motion

































| | Reference number | Description |
|---|------------------|---|
|  | 25100 | Motion detector, 230 V, 10 m, 180°, IP44, wall detector, for flush-mounting box |
|  | 25480 | Motion detector, 230 V, 7 m, IP44, mini, for flush mounting |
|  | 25341 | Motion detector, 230 V, 14 m, round, for flush-mounting box |
|  | 25342 | Motion detector, 230 V, 14 m, round, for flush-mounting box |
|  | 25000 | Motion detector, 230 V, 14 m, square, for flush-mounting box |
|  | 25471 | Motion detector, 230 V, 8 m, IP54, for flush-mounting box |
|  | 25478 | Motion detector, 230 V, master, 12 m, IP54, mini, for flush mounting |
|  | 25476 | Motion detector, 230 V, master, 12 m, IP54, mini, for flush mounting |
|  | 25290D | Motion detector, 230 V, 10 m, 180°, wall detector, for flush-mounting box |
|  | 25230 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box |
|  | 25231 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box |
|  | 25232 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box |
|  | 25236 | Motion detector, 230 V, 10 m, 180°, IP55, for surface mounting |
|  | 25491 | Motion detector, 230 V, 10 m, 180°, IP44, mini, for flush mounting |
|  | 3327 | Motion detector, 230 V, 12 m, IP44, for surface mounting |
|  | 3321 | Motion detector, acoustics, 230 V, 8 m, for surface mounting |
|  | 3322 | Motion detector, acoustics, 230 V, 20 m, for flush-mounting box |
|  | 3220 | Motion detector, 230 V, 8 m, 180°, wall detector, for flush-mounting box |






























| | Master/Secondary | Protection degree | Number of channels/ number of zones | Detection angle | Mounting height | Detection range | Commissioning method 1 | Commissioning method 2 | Commissioning method 3 | Page |
|--------|------------------|-------------------|--|-----------------|-----------------|-----------------|------------------------|------------------------|------------------------|------|
| - | IP44 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 8 |
| - | IP44 | 1 channel | 360° | 2 – 5 m | ø 7 m | Remote control | App + Universal RC | | | 8 |
| - | IP20 | 1 channel | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | | 8 |
| - | IP20 | 1 channel | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | | 8 |
| - | IP20 | 1 channel | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | | 8 |
| - | IP54 | 1 channel | 360° | 2 – 5 m | ø 8 m | Remote control | App + Universal RC | | | 8 |
| Master | IP54 | 1 channel | 360° | 2 – 5 m | ø 12 m | Remote control | App + Universal RC | | | 9 |
| Master | IP54 | 1 channel | 360° | 2 – 5 m | ø 12 m | Remote control | App + Universal RC | | | 9 |
| - | IP20 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 9 |
| - | IP55 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 9 |
| - | IP55 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 9 |
| - | IP55 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 9 |
| - | IP55 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | | 10 |
| - | IP44 | 1 channel | 180° | 1 – 2.5 m | 10 m | Remote control | App + Universal RC | | | 10 |
| - | IP44 | 1 channel | 360° | 2 – 4 m | ø 12 m | On the device | | | | 10 |
| - | IP20 | 1 channel | 360° | 2 – 4 m | ø 8 m | On the device | | | | 10 |
| - | IP20 | 1 channel | 360° | 2 – 4 m | ø 20 m | On the device | | | | 10 |
| - | IP20 | 1 channel | 180° | 1 – 1.5 m | 8 m | On the device | | | | 10 |













| Article number | Description | | | | |
|--|---|---|---|--|---|
|  25100 | Motion detector, 230 V, 10 m, 180°, IP44, wall detector, for flush-mounting box, white |  N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  flush-mounting box |
| <p>Wall-mounted motion detector from 1.0 to 3.0 m. Possible thanks to its horizontal and vertical detection range. With screwed cover, ideal for public buildings. External switch (ON). Finishing colour: white</p> | | | | | |
|  25480 | Motion detector, 230 V, 7 m, IP44, mini, for flush mounting, white |  N.O. (max. 10 A) |  PIR: ø 7 m from a height of 3 m |  2 – 5 m |  flush-mounting |
| <p>Motion detector with minimal space requirement, very small dimensions and remote electronics. Configuration only with PIR remote control or app and universal remote control. External switch (ON). Finishing colour: white</p> | | | | | |
|  25341 | Motion detector, 230 V, 14 m, round, for flush-mounting box, black |  N.O. (max. 10 A) |  PIR: ø 14 m from a height of 3 m |  2 – 6 m |  flush-mounting box |
| <p>Motion detector with strong detection, for universal use thanks to versatile accessories, external switch (ON). Ideal for passageways. Finishing colour: black</p> | | | | | |
|  25342 | Motion detector, 230 V, 14 m, round, for flush-mounting box, alu |  N.O. (max. 10 A) |  PIR: ø 14 m from a height of 3 m |  2 – 6 m |  flush-mounting box |
| <p>Motion detector with strong detection, for universal use thanks to versatile accessories, external switch (ON). Ideal for passageways. Finishing colour: alu</p> | | | | | |
|  25000 | Motion detector, 230 V, 14 m, square, for flush-mounting box, white |  N.O. (max. 10 A) |  PIR: ø 14 m from a height of 3 m |  2 – 6 m |  flush-mounting box |
| <p>Motion detector with strong detection, for universal use thanks to versatile accessories, external switch (ON). Ideal for passageways, Finishing colour: white</p> | | | | | |
|  25471 | Motion detector, 230 V, 8 m, IP54, for flush-mounting box, white |  N.O. (max. 10 A) |  PIR: ø 8 m from a height of 4 m |  2 – 5 m |  flush-mounting box |
| <p>Detector with a flat design, a variable detection range and an external switch input. Mounting in flush-mounting box. Configuration only with PIR remote control or app and universal remote control. External switch (ON). Finishing colour: white</p> | | | | | |

| Article number | Description | | | | |
|--|---|--|---|--|---|
|  25478 | Motion detector, 230 V, master, 12 m, IP54, mini, for flush mounting, white |  MASTER N.O. (max. 10 A) |  PIR: ø 12 m from a height of 3 m |  2 – 5 m |  flush-mounting |
| Motion detector with super flat design and external switch input. Ideal for mounting in profile rails or wet rooms. Configuration only with PIR remote control or app and universal remote control. External switch (ON). Finishing colour: white | | | | | |
|  25476 | Motion detector, 230 V, master, 12 m, IP54, mini, for flush mounting, black |  MASTER N.O. (max. 10 A) |  PIR: ø 12 m from a height of 3 m |  2 – 5 m |  flush-mounting |
| Motion detector with super flat design and external switch input. Ideal for mounting in profile rails or wet rooms. Configuration only with PIR remote control or app and universal remote control. External switch (ON). Finishing colour: black | | | | | |
|  25290D | Motion detector, 230 V, 10 m, 180°, wall detector, for flush-mounting box, white |  STAND-ALONE N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  flush-mounting box |
| Wall-mounted motion detector from 1.0 to 3.0 m. Possible thanks to its horizontal and vertical detection range. Ideal for stairwells, corridors, basements, garages, etc. External switch (ON). Finishing colour: white | | | | | |
|  25230 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box, white |  STAND-ALONE N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  flush-mounting box |
| Motion detector with increased splash protection for wall mounting from 1.0 to 3.0 m, possible thanks to its horizontal and vertical detection range. Ideal for wet rooms and outdoor use. External switch (ON). Finishing colour: white | | | | | |
|  25231 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box, black |  STAND-ALONE N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  flush-mounting box |
| Motion detector with increased splash protection for wall mounting from 1.0 to 3.0 m, possible thanks to its horizontal and vertical detection range. Ideal for wet rooms and outdoor use. External switch (ON). Finishing colour: black | | | | | |
|  25232 | Motion detector, 230 V, 10 m, 180°, IP55, wall detector, for flush-mounting box, grey |  STAND-ALONE N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  flush-mounting box |
| Motion detector with increased splash protection for wall mounting from 1.0 to 3.0 m, possible thanks to its horizontal and vertical detection range. Ideal for wet rooms and outdoor use. External switch (ON). Finishing colour: grey | | | | | |



| Article number | Description | | | | |
|---|---|---|---|--|---|
|  | 25236 Motion detector, 230 V, 10 m, 180°, IP55, for surface mounting, black |  N.O. (max. 10 A) |  PIR: 10 m from a height of 3 m |  1 – 3 m |  surface mounting |
| Motion detector with increased splash protection for wall mounting from 1.0 to 3.0 m, possible thanks to its horizontal and vertical detection range. Ideal for wet rooms and outdoor use. External switch (ON). Finishing colour: black | | | | | |
|  | 25491 Motion detector, 230 V, 10 m, 180°, IP44, mini, for flush mounting, black |  N.O. (max. 10 A) |  PIR: 10 m from a height of 2.5 m |  1 – 2.5 m | |
| Motion detector for installation with minimal space requirement, very small dimensions and remote electronics. Configuration only with PIR remote control or app. External switch (ON). Finishing colour: black | | | | | |
|  | 3327 Motion detector, 230 V, 12 m, IP44, for surface mounting, white |  N.O. (max. 4.35 A) |  PIR: ø 12 m from a height of 3 m |  2 – 4 m |  surface mounting |
| Economical motion detector for simple applications. Finishing colour: white | | | | | |
|  | 3321 Motion detector, acoustics, 230 V, 8 m, for surface mounting, white |  N.O. (max. 4.35 A) |  PIR: ø 8 m from a height of 3 m |  2 – 4 m |  surface mounting |
| Dual-technology motion detector (PIR and acoustic). Ideal for toilets, changing rooms, etc. Finishing colour: white | | | | | |
|  | 3322 Motion detector, acoustics, 230 V, 20 m, for flush-mounting box, white |  N.O. (max. 4.35 A) |  PIR: ø 20 m from a height of 3 m |  2 – 4 m |  flush-mounting box |
| Dual-technology motion detector (PIR and acoustic) with broad detection range. Ideal for toilets, changing rooms, etc. External switch (ON). Finishing colour: white | | | | | |
|  | 3220 Motion detector, 230 V, 8 m, 180°, wall detector, for flush-mounting box, white |  N.O. (max. 4.35 A) |  PIR: 8 m from a height of 1.1 m |  1 – 1.5 m |  flush-mounting box |
| Economical motion detector for simple applications. The lighting can be manually controlled with the built-in switch (slide switch). Finishing colour: white | | | | | |

Accessories

| Article number | Description |
|---|---|
|  25276 | Flush-mounting 360 housing RA, IP55, 16 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25273 | Surface-mounting box, IP55, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25274 | Surface-mounting box, IP55, black Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25421 | Frame for surface mounting RA, IP44, round, white Surface-mounting synthetic frame, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25330 | Deco ring, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-25469, 351-26004 |
|  25264 | Surface-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25267 | Flush-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25335 | Cover plate RA, 30 m, round, white Compatible articles: 351-25065, 351-25459, 351-25467, 351-25469, 351-26002 |
|  25400 | Flush surround plate for surface mounting, square, white Compatible articles: 351-25451, 351-26001, 351-26003 |
|  25411 | Flush mounting box with spring clips Compatible articles: 351-25065, 351-25340, 351-25451, 351-25457, 351-25459, 351-25463, 351-25467, 351-25469, 351-26001, 351-26002, 351-26003, 351-26004 |



Article number **Description****25323****Universal remote control with lux meter**

In combination with the universal remote control, detectors can easily be configured through the app. All values and detector functions of all detectors can be controlled easily and quickly from a smartphone or tablet and adjusted to the circumstances on site. Compatible articles: 350-20072, 350-20082, 350-41657, 350-41750, 350-41751, 350-41753, 350-41761, 351-25050, 351-25065, 351-25340, 351-25451, 351-25457, 351-25463, 351-25467, 351-25475, 351-25480, 351-26001, 351-26002, 351-26003, 351-26004, 351-26450, 351-26470, 351-26480, 351-26560, 351-26562, 351-26570, 351-26572

**25013****Flush-mounting box kit DA, white**

Flush-mounting box kit for ceilings.
Finishing colour: white

**25270UP****Set for flush mounting, IP55, white**










230 V presence

































Reference number






Description

| | | |
|---|--------|--|
|  | 41721 | Presence detector, 230 V, master, 2 channels, 24 m, IP54, for surface mounting |
|  | 25474 | Presence detector, dual tech, PIR+HF, 230 V, master, 40 m / 12 m, IP54, for flush mounting |
|  | 25452 | Presence detector, 230 V, master, 14 m, IP44, for surface mounting |
|  | 25453 | Presence detector, 230 V, secondary, 14 m, IP44, for surface mounting |
|  | 25170 | Presence detector, 230 V, 14 m, for flush mounting |
|  | 25210D | Presence detector, 230 V, 10 m, 180°, wall detector, for flush-mounting box |
|  | 25395D | Presence detector, 230 V, 10 m, 180°, with integrated switch, Max, wall detector, for flush-mounting box |








| | Master/Secondary | Protection degree | Number of channels/ number of zones | Detection angle | Mounting height | Detection range | Commissioning method 1 | Commissioning method 2 | Commissioning method 3 | Page |
|-----------|------------------|-------------------|--|-----------------|---------------------|-----------------|------------------------|------------------------|------------------------|------|
| Master | IP54 | 2 channels | 360° | 2 – 3,4 m | ø 24 m | On the device | Remote control | App + Universal RC | 18 | |
| Master | IP54 | 1 channel | 360° | 2 – 4 m | ø 40 m (HF: ø 12 m) | On the device | Remote control | App + Universal RC | 18 | |
| Master | IP44 | 1 channel | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | 18 | |
| Secondary | IP44 | - | 360° | 2 – 6 m | ø 14 m | On the device | | | 18 | |
| - | IP20 | 1 channel | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | 18 | |
| - | IP20 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | 18 | |
| - | IP20 | 1 channel | 180° | 1 – 3 m | 10 m | On the device | Remote control | App + Universal RC | 19 | |








| Article number | Description | | | | |
|---|---|---|---|---|---|
|  41721 | Presence detector, 230 V, master, 2 channels, 24 m, IP54, for surface mounting, white |  |  |  |  |
| | | 2 x N.O. (max. 10 A), potential-free | PIR: ø 24 m from a height of 3 m | 2 – 3.4 m | surface mounting |
| | Master presence detector with increased detection range, 2x external switch input, full and semi-automatic mode, two potential-free switch outputs to switch 2 conventional lighting strips or 1x lighting plus 1x HVAC. The lux level (lux) can be freely chosen for each channel (lighting or HVAC). Range extension with up to 10 secondary detectors. Finishing colour: white | | | | |
|  25474 | Presence detector, dual tech, PIR+HF, 230 V, master, 40 m / 12 m, IP54, for flush mounting, white |  |  |  |  |
| | | N.O. (max. 10 A), potential-free | PIR: ø 40 m from a height of 3 m HF: ø 12 m from a height of 3 m | 2 – 4 m | flush-mounting |
| | Dual-technology master presence detector (HF and PIR). Detection behaviour can be chosen by means of five different logical combinations of PIR and HF. Thanks to the innovative combination of HF and PIR technology, the sensitivity can be optimally adjusted to the specific situation. External switch input, full and semi-automatic mode, potential-free switch output. Range extension with a maximum of 10 secondary detectors. Finishing colour: white | | | | |
|  25452 | Presence detector, 230 V, master, 14 m, IP44, for surface mounting, white |  |  |  |  |
| | | N.O. (max. 8.7 A) | PIR: ø 14 m from a height of 3 m | 2 – 6 m | surface mounting |
| | Master presence detector with external switch input as well as full and semi-automatic mode. For surface mounting/ceiling mounting with increased splash protection. Finishing colour: white | | | | |
|  25453 | Presence detector, 230 V, secondary, 14 m, IP44, for surface mounting, white |  |  |  |  |
| | | | PIR: ø 14 m from a height of 3 m | 2 – 6 m | surface mounting |
| | Secondary presence detector for range extension of master ceiling and wall detectors. For surface mounting/ceiling mounting with increased splash protection. Finishing colour: white | | | | |
|  25170 | Presence detector, 230 V, 14 m, for flush mounting, white |  |  |  |  |
| | | N.O. (max. 10 A) | PIR: ø 14 m from a height of 3 m | 2 – 6 m | flush-mounting |
| | Presence detector with flat, modern design for suspended ceilings. Mounted with spring clips. External switch (ON). Finishing colour: white | | | | |
|  25210D | Presence detector, 230 V, 10 m, 180°, wall detector, for flush-mounting box, white |  |  |  |  |
| | | N.O. (max. 10 A) | PIR: 10 m from a height of 3 m | 1 – 3 m | flush-mounting box |
| | Presence detector for lounge areas and offices as well as stairwells, external switch only to switch on. Wall mounting from 1.0–3.0 m, possible thanks to 3 PIR sensors (elimination of creeping zones). Finishing colour: white | | | | |

| Article number | Description | |
|---|--|--|
|  25395D | Presence detector, 230 V, 10 m, 180°, with integrated switch, Max, wall detector, for flush-mounting box, white |  STAND-ALONE N.O. (max. 8.7 A)  PIR: 10 m from a height of 3 m  1 – 3 m  flush-mounting box |
| <p>Presence detector with invisible screw attachment, especially suitable for public areas. Wall mounting from 1 to 3 m possible thanks to its horizontal and vertical detection range. Finishing colour: white</p> | | |

Accessories

| Article number | Description |
|--|--|
|  25323 | Universal remote control with lux meter In combination with the universal remote control, detectors can easily be configured through the app. All values and detector functions of all detectors can be controlled easily and quickly from a smartphone or tablet and adjusted to the circumstances on site. Compatible articles: 350-20072, 350-20082, 350-41657, 350-41750, 350-41751, 350-41753, 350-41761, 351-25050, 351-25065, 351-25340, 351-25451, 351-25457, 351-25463, 351-25467, 351-25475, 351-25480, 351-26001, 351-26002, 351-26003, 351-26004, 351-26450, 351-26470, 351-26480, 351-26560, 351-26562, 351-26570, 351-26572 |
|  25400 | Flush surround plate for surface mounting, square, white Compatible articles: 351-25451, 351-26001, 351-26003 |
|  25411 | Flush mounting box with spring clips Compatible articles: 351-25065, 351-25340, 351-25451, 351-25457, 351-25459, 351-25463, 351-25467, 351-25469, 351-26001, 351-26002, 351-26003, 351-26004 |
|  25264 | Surface-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25267 | Flush-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25335 | Cover plate RA, 30 m, round, white Compatible articles: 351-25065, 351-25459, 351-25467, 351-25469, 351-26002 |
|  25421 | Frame for surface mounting RA, IP44, round, white Surface-mounting synthetic frame, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |



| Article number | Description |
|--|---|
|  25276 | Flush-mounting 360 housing RA, IP55, 16 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25273 | Surface-mounting box, IP55, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25274 | Surface-mounting box, IP55, black Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25330 | Deco ring, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-25469, 351-26004 |
|  25270UP | Set for flush mounting, IP55, white |





DALI



Reference number

Description



26002

Presence detector, DALI, master, 30 m, round, for flush-mounting box



26003

Presence detector, DALI, master, 14 m, square, for flush-mounting box


















26004





Presence detector, DALI, master, 14 m, round, for flush-mounting box









| | Master/Secondary | Protection degree | Number of channels/ number of zones | Detection angle | Mounting height | Detection range | Commissioning method 1 | Commissioning method 2 | Commissioning method 3 | Page |
|--------|------------------|-------------------|--|-----------------|-----------------|-----------------|------------------------|------------------------|------------------------|------|
| Master | IP20 | 1 zone | 360° | 2 – 8 m | ø 30 m | On the device | Remote control | App + Universal RC | 26 | |
| Master | IP20 | 1 zone | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | 26 | |
| Master | IP20 | 1 zone | 360° | 2 – 6 m | ø 14 m | On the device | Remote control | App + Universal RC | 26 | |



| Article number | Description | |
|--|---|--|
|  26002 | Presence detector, DALI, master, 30 m, round, for flush-mounting box, white |     MASTER 1 PIR: ø 30 m from a height of 8 m 2 – 8 m flush-mounting box |
| <p>Master presence detector with increased range for DALI systems (broadcast). daylight control for 1 zone. Easy to start up via app, remote control or controller. Max. 10 secondary detectors are wired by means of a control cable. Finishing colour: white</p> | | |
|  26003 | Presence detector, DALI, master, 14 m, square, for flush-mounting box, white |     MASTER 1 PIR: ø 14 m from a height of 3 m 2 – 6 m flush-mounting box |
| <p>Master presence detector for DALI systems (broadcast). daylight control for 1 zone. Easy to start up via app, remote control or controller. Max. 10 secondary detectors are wired by means of a control cable. Finishing colour: white</p> | | |
|  26004 | Presence detector, DALI, master, 14 m, round, for flush-mounting box, white |     MASTER 1 PIR: ø 14 m from a height of 3 m 2 – 6 m flush-mounting box |
| <p>Master presence detector for DALI systems (broadcast). daylight control for 1 zone. Easy to start up via app, remote control or controller. Max. 10 secondary detectors are wired by means of a control cable. Finishing colour: white</p> | | |

Accessories

| Article number | Description |
|--|---|
|  25323 | Universal remote control with lux meter <p>In combination with the universal remote control, detectors can easily be configured through the app. All values and detector functions of all detectors can be controlled easily and quickly from a smartphone or tablet and adjusted to the circumstances on site. Compatible articles: 350-20072, 350-20082, 350-41657, 350-41750, 350-41751, 350-41753, 350-41761, 351-25050, 351-25065, 351-25340, 351-25451, 351-25457, 351-25463, 351-25467, 351-25475, 351-25480, 351-26001, 351-26002, 351-26003, 351-26004, 351-26450, 351-26470, 351-26480, 351-26560, 351-26562, 351-26570, 351-26572</p> |
|  25351 | PIR DALI remote control <p>Compatible articles: 351-26001, 351-26002, 351-26003, 351-26004</p> |
|  25264 | Surface-mounting 360 housing RA, IP55, 30 m, round, white <p>High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002</p> |
|  25267 | Flush-mounting 360 housing RA, IP55, 30 m, round, white <p>High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002</p> |

| Article number | Description |
|---|---|
|  25335 | Cover plate RA, 30 m, round, white Compatible articles: 351-25065, 351-25459, 351-25467, 351-25469, 351-26002 |
|  25411 | Flush mounting box with spring clips Compatible articles: 351-25065, 351-25340, 351-25451, 351-25457, 351-25459, 351-25463, 351-25467, 351-25469, 351-26001, 351-26002, 351-26003, 351-26004 |
|  25400 | Flush surround plate for surface mounting, square, white Compatible articles: 351-25451, 351-26001, 351-26003 |
|  25273 | Surface-mounting box, IP55, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25274 | Surface-mounting box, IP55, black Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25330 | Deco ring, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-25469, 351-26004 |
|  25276 | Flush-mounting 360 housing RA, IP55, 16 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25421 | Frame for surface mounting RA, IP44, round, white Surface-mounting synthetic frame, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |

















KNX























Reference number

Description

| | | |
|---|--------|---|
|  | 25032 | Presence detector, KNX, 2 channels, 14 m, for flush-mounting box |
|  | 25034 | Presence detector, KNX, 2 channels, 14 m, for flush mounting |
|  | 25020N | Presence detector, KNX, 16 m, for flush-mounting box |
|  | 25010 | Motion detector, KNX, 2 channels, 8 m, IP54, for flush mounting |
|  | 25240D | Presence detector, KNX, 2 channels, 10 m, 180°, wall detector, for flush-mounting box |
|  | 25241 | Presence detector, KNX, 2 channels, 10 m, 180°, IP55, wall detector, for flush-mounting box |
|  | 25245 | Presence detector, KNX, 2 channels, 10 m, 180°, IP55, wall detector, for flush-mounting box |
|  | 25242 | Presence detector, KNX, 2 channels, 10 m, 180°, IP55, for surface mounting |
|  | 25248 | Presence detector, KNX, 2 channels, 10 m, 180°, IP55, for surface mounting |
|  | 25036 | Presence detector, KNX, 2 channels, 26 m, for flush-mounting box |

| Master/Secondary | Protection degree | Number of channels/ number of zones | Detection angle | Mounting height | Detection range | Commissioning method | Page |
|------------------|-------------------|--|-----------------|-----------------|-----------------|----------------------|------|
| Master/Secondary | IP20 | 2 channels | 360° | 2 – 6 m | ø 14 m | ETS software | 32 |
| Master/Secondary | IP20 | 2 channels | 360° | 2 – 6 m | ø 14 m | ETS software | 32 |
| - | IP20 | 1 channel | 360° | 2 – 10 m | ø 16 m | ETS software | 32 |
| Master/Secondary | IP54 | 2 channels | 360° | 2 – 5 m | ø 8 m | ETS software | 32 |
| Master/Secondary | IP20 | 2 channels | 180° | 1 – 2.2 m | 10 m | ETS software | 32 |
| Master/Secondary | IP55 | 2 channels | 180° | 1 – 3 m | 10 m | ETS software | 33 |
| Master/Secondary | IP55 | 2 channels | 180° | 1 – 3 m | 10 m | ETS software | 33 |
| Master/Secondary | IP55 | 2 channels | 180° | 1 – 3 m | 10 m | ETS software | 33 |
| Master/Secondary | IP55 | 2 channels | 180° | 1 – 3 m | 10 m | ETS software | 33 |
| Master/Secondary | IP20 | 2 channels | 360° | 2 – 8 m | ø 26 m | ETS software | 33 |



| Article number | Description | |
|--|---|--|
|  25032 | Presence detector, KNX, 2 channels, 14 m, for flush-mounting box, white |    <p>PIR: ø 14 m from a height of 3 m 2 – 6 m flush-mounting box</p> |
| <p>Master-secondary presence detector for universal use thanks to versatile accessories. daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.</p> <p>Finishing colour: white Compatible secondary detectors: /</p> | | |
|  25034 | Presence detector, KNX, 2 channels, 14 m, for flush mounting, white |    <p>PIR: ø 14 m from a height of 3 m 2 – 6 m flush-mounting</p> |
| <p>Master-secondary presence detector with spring clip adapter for fast mounting in suspended ceilings. Daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.</p> <p>Finishing colour: white Compatible secondary detectors: /</p> | | |
|  25020N | Presence detector, KNX, 16 m, for flush-mounting box, white |    <p>PIR: ø 16 m from a height of 3 m 2 – 10 m flush-mounting box</p> |
| <p>Presence detector with ground functionality, 1 light channel for daylight control (only KLR version) or 1 light channel for ON/OFF, HVAC, full and semi-automatic mode.</p> <p>Finishing colour: white</p> | | |
|  25010 | Motion detector, KNX, 2 channels, 8 m, IP54, for flush mounting, white |    <p>PIR: ø 8 m from a height of 4 m 2 – 5 m flush-mounting</p> |
| <p>Master-secondary motion detector, ideal for mounting in profile rails or wet rooms. Daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.</p> <p>Finishing colour: white Compatible secondary detectors: /</p> | | |
|  25240D | Presence detector, KNX, 2 channels, 10 m, 180°, wall detector, for flush-mounting box, white |    <p>PIR: 10 m from a height of 3 m 1 – 2.2 m flush-mounting box</p> |
| <p>Master-secondary presence detector, wall mounting from 1.0 to 3.0 m possible thanks to its horizontal and vertical detection range, daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.</p> <p>Finishing colour: white Compatible secondary detectors: /</p> | | |

| Article number | Description |
|----------------|-------------|
|----------------|-------------|

**25241**

Presence detector, KNX, 2 channels, 10 m, 180°, IP55, wall detector, for flush-mounting box, white



Master-secondary presence detector, wall mounting from 1.0 to 3.0 m possible thanks to its horizontal and vertical detection range, daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: white

Compatible secondary detectors: /

**25245**

Presence detector, KNX, 2 channels, 10 m, 180°, IP55, wall detector, for flush-mounting box, black



Master-secondary presence detector, wall mounting from 1.0 to 3.0 m possible thanks to its horizontal and vertical detection range, daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: black

Compatible secondary detectors: /

**25242**

Presence detector, KNX, 2 channels, 10 m, 180°, IP55, for surface mounting, white



Master-secondary presence detector, wall mounting from 1.0 to 3.0 m possible thanks to its horizontal and vertical detection range, daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: white

Compatible secondary detectors: /

**25248**

Presence detector, KNX, 2 channels, 10 m, 180°, IP55, for surface mounting, black



Master-secondary presence detector, wall mounting from 1.0 to 3.0 m possible thanks to its horizontal and vertical detection range, daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: black

Compatible secondary detectors: /

**25036**

Presence detector, KNX, 2 channels, 26 m, for flush-mounting box, white













Master-secondary presence detector with increased range for universal use thanks to versatile accessories. Daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: white

Compatible secondary detectors: /



Accessories

| Article number | Description |
|---|---|
|  25276 | Flush-mounting 360 housing RA, IP55, 16 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25330 | Deco ring, white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-25469, 351-26004 |
|  25421 | Frame for surface mounting RA, IP44, round, white Surface-mounting synthetic frame, splash protection. Finishing colour: white Compatible articles: 351-25340, 351-25457, 351-25459, 351-25463, 351-26004 |
|  25013 | Flush-mounting box kit DA, white Flush-mounting box kit for ceilings. Finishing colour: white |
|  25270UP | Set for flush mounting, IP55, white |
|  25400 | Flush surround plate for surface mounting, square, white Compatible articles: 351-25451, 351-26001, 351-26003 |
|  25264 | Surface-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25267 | Flush-mounting 360 housing RA, IP55, 30 m, round, white High-quality synthetic housing, splash protection. Finishing colour: white Compatible articles: 351-25065, 351-25467, 351-25469, 351-26002 |
|  25335 | Cover plate RA, 30 m, round, white Compatible articles: 351-25065, 351-25459, 351-25467, 351-25469, 351-26002 |
|  25411 | Flush mounting box with spring clips Compatible articles: 351-25065, 351-25340, 351-25451, 351-25457, 351-25459, 351-25463, 351-25467, 351-25469, 351-26001, 351-26002, 351-26003, 351-26004 |



24 V



Reference number

Description








25468




Presence detector, 24 V, 14 m, for flush-mounting box

| | | | | | | | | | |
|------------------|-------------------|--|-----------------|-----------------|-----------------|------------------------|------------------------|------------------------|------|
| Master/Secondary | Protection degree | Number of channels/ number of zones | Detection angle | Mounting height | Detection range | Commissioning method 1 | Commissioning method 2 | Commissioning method 3 | Page |
| - | IP20 | 1 channel | 360° | 2 – 8 m | ø 14 m | On the device | Remote control | App + Universal RC | 40 |



| Article number | Description | |
|---|--|---|
|  25468 | Presence detector, 24 V, 14 m, for flush-mounting box, white |     |
| | Presence detector for 24 V supply with potential-free switch contact. For universal use thanks to versatile accessories. Ideal for applications in building automation systems. External switch (ON). Finishing colour: white | |

Accessories

| Article number | Description |
|---|--|
|  25323 | Universal remote control with lux meter In combination with the universal remote control, detectors can easily be configured through the app. All values and detector functions of all detectors can be controlled easily and quickly from a smartphone or tablet and adjusted to the circumstances on site. Compatible articles: 350-20072, 350-20082, 350-41657, 350-41750, 350-41751, 350-41753, 350-41761, 351-25050, 351-25065, 351-25340, 351-25451, 351-25457, 351-25463, 351-25467, 351-25475, 351-25480, 351-26001, 351-26002, 351-26003, 351-26004, 351-26450, 351-26470, 351-26480, 351-26560, 351-26562, 351-26570, 351-26572 |
|  25400 | Flush surround plate for surface mounting, square, white Compatible articles: 351-25451, 351-26001, 351-26003 |
|  25411 | Flush mounting box with spring clips Compatible articles: 351-25065, 351-25340, 351-25451, 351-25457, 351-25459, 351-25463, 351-25467, 351-25469, 351-26001, 351-26002, 351-26003, 351-26004 |

| Reference number | Page | Reference number | Page | Reference number | Page |
|------------------|--------------------|------------------|------|------------------|------|
| 3000 | | | | | |
| 3220 | 16 | | | | |
| 3321 | 16 | | | | |
| 3322 | 16 | | | | |
| 3327 | 16 | | | | |
| 7000 | | | | | |
| 7520 | 8 | | | | |
| 24000 | | | | | |
| 25000 | 14 | | | | |
| 25000 | | | | | |
| 25010 | 38 | | | | |
| 25013 | 18, 40 | | | | |
| 25020N | 38 | | | | |
| 25032 | 38 | | | | |
| 25034 | 38 | | | | |
| 25036 | 39 | | | | |
| 25100 | 14 | | | | |
| 25170 | 24 | | | | |
| 25210D | 24 | | | | |
| 25230 | 15 | | | | |
| 25231 | 15 | | | | |
| 25232 | 15 | | | | |
| 25236 | 16 | | | | |
| 25240D | 38 | | | | |
| 25241 | 39 | | | | |
| 25242 | 39 | | | | |
| 25245 | 39 | | | | |
| 25248 | 39 | | | | |
| 25264 | 17, 25, 32, 40 | | | | |
| 25267 | 17, 25, 32, 40 | | | | |
| 25270UP | 18, 26, 40 | | | | |
| 25273 | 17, 26, 33 | | | | |
| 25274 | 17, 26, 33 | | | | |
| 25276 | 17, 26, 33, 40 | | | | |
| 25290D | 15 | | | | |
| 25323 | 18, 25, 32, 46 | | | | |
| 25330 | 17, 26, 33, 40 | | | | |
| 25335 | 17, 25, 33, 40 | | | | |
| 25341 | 14 | | | | |
| 25342 | 14 | | | | |
| 25351 | 32 | | | | |
| 25395D | 25 | | | | |
| 25400 | 17, 25, 33, 40, 46 | | | | |
| 25411 | 17, 25, 33, 40, 46 | | | | |
| 25421 | 17, 25, 33, 40 | | | | |
| 25452 | 24 | | | | |
| 25453 | 24 | | | | |
| 25468 | 46 | | | | |
| 25471 | 14 | | | | |
| 25474 | 24 | | | | |
| 25476 | 15 | | | | |
| 25478 | 15 | | | | |
| 25480 | 14 | | | | |
| 25491 | 16 | | | | |
| 26000 | | | | | |
| 26002 | 32 | | | | |
| 26003 | 32 | | | | |
| 26004 | 32 | | | | |
| 41000 | | | | | |
| 41721 | 24 | | | | |

Reference number

Page

Reference number












Page

Reference number

Page



Key

| | | | |
|---|---|---|--------------------------------------|
|  |  | The maximum detection range when correctly installed | |
|  |  | The minimum and maximum mounting height of the detector | |
|  |  |  | The correct mounting of the detector |
|  | Wall detector | | |
|  | The detector contains a relay contact | | |
|  | Light sensitivity | | |
|  | Waterproof level | | |

Contact us

If you require more information, contact Niko Sales at sales.be@niko.eu or +32 3 778 90 20.

When you are ready to place your order, send an e-mail to Expedition_Central@niko.eu.



Aktuelle Informationen
finden Sie auf www.niko.eu

Niko designs electr(on)ic solutions to enhance buildings to better suit the needs of the people who live and work in them. By using less energy, by improving light comfort and safety and by making sure all applications work together seamlessly. Buildings with Niko are more efficient, are controllable from a distance and interact within bigger ecosystems. Niko is a Belgian family business from Sint-Niklaas with 700 employees and 10 European branches.

At Niko, there is one question that keeps us busy every day: “How can we enhance buildings to better suit your needs?”

nv Niko sa
Industriepark West 40
9100 Sint-Niklaas
Belgium
sales.be@niko.eu
+32 3 778 90 00
www.niko.eu

niko



PRONODIS
Soluções Tecnológicas, Lda.

detetamos soluções